

IGH TS & QS

Model Name	QS-RC5	TS-RC5	TS-RF5
Model No.	IHQ5C.QBLS.AA3	IHT5C.QBSS.AA0	IHT5F.QBSC.AA1
Speed	5-Speed + Reverse	5-Speed	5-Speed
Type	Coaster Brake	Coaster Brake	Freewheel
Hub Shell Material	6061 Aluminum	6061 Aluminum	6061 Aluminum
Gear Ratio	Overall Range	256%	
	1	62.5%	(-) 37.5%
	2	75%	(-) 25% [Gear 1 (+) 20%]
	3	100%	Direct Drive [Gear 2 (+) 33%]
	4	133.3%	(+) 33.3% [Gear 3 (+) 33%]
	5	160%	(+) 60% [Gear 4 (+) 20%]
Axle Diameter	13/32" Slotted	13/32" Slotted	13/32" Slotted
Axle Length	185mm	175mm	175mm
Over Locknut Dimension	139mm	127mm	116mm
R: Axle Protrusion Length	24mm	24mm	24mm
L: Axle Protrusion Length	22mm	24mm	35mm
Flange Sprocket Teeth	22T	22T	22T
Flange Sprocket C.L.	39.4mm	33.9mm	27.6mm
Sprocket Teeth	21~22T	21~22T	21~22T
Sprocket Chain Line	53.9mm	51.5mm	44.2mm
Indicators	Yellow / Navy Blue*	Yellow / Navy Blue*	Yellow / Navy Blue*
Finish	Anodized Alloy	Anodized Alloy	Anodized Alloy
Weight	2,010g	1,580g	1,320g

*Navy Blue Indicator must be used when using HMN420 Short Guide Nut.

IGH TS & QS

Model Name	QS-RC3	TS-RC3	TS-RF3	T-S2C
Model No.	IHQ3C.QBLS.AA3	IHT3C.QBSS.AA3	IHT3F.QBSS.AA3	IHT2C.SBSS.AA1
Speed	3-Speed + Reverse	3-Speed	3-Speed	2-Speed
Type	Coaster Brake	Coaster Brake	Freewheel	Coaster Brake
Hub Shell Material	6061 Aluminum	6061 Aluminum	6061 Aluminum	6061 Aluminum
Gear Ratio	Overall Range	177%		138%
	1	75%	(-) 25%	100% Direct Drive
	2	100%	Direct Drive [Gear 1 (+) 33%]	138% (+) 38%
	3	133%	(+) 33.3% [Gear 2 (+) 33%]	×
Axle Diameter	13/32" Slotted			13/32" Slotted
Axle Length	175mm	163mm	163mm	162mm
Over Locknut Dimension	126mm	116mm	117mm	116mm
R: Axle Protrusion Length	30mm	26mm	22mm	23mm
L: Axle Protrusion Length	19mm	21mm	24mm	23mm
Flange Sprocket Teeth	22T	22T	22T	22T
Flange Sprocket C.L.	33.4mm	27.8mm	30.1mm	27.8mm
Sprocket Teeth	21~22T	21~22T	21~22T	21~22T
Sprocket Chain Line	47.2mm	45.7mm	44.9mm	45.7mm
Indicators	MK5	MK4	MK3	×
Finish	Anodized Alloy	Anodized Alloy	Anodized Alloy	Hi-Polished Anodized
Weight	1,800g	1,360g	1,100g	1,465g